



M3 DFT Classic® Series Filter Cartridges

High Capacity Depth Filter Cartridges With Positive Double O-ring Sealing

- Double O-ring sealing effectively eliminates potential fluid bypass in most applications
- No epoxies or glues to contaminate fluid streams
- Fits most standard 222 O-ring housings
- Wide range of retention ratings to meet specific application requirements
- Inexpensive alternative to pleated cartridges
- Polypropylene or cotton media suitable for a wide range of applications
- Extends life of expensive final filters in many applications

Performance Specifications

Filter grades

0.5, 1, 3, 5, 10, 25 µm

Maximum differential pressure

3.45 bard @ 25°C (50 psid @ 77°F)

Maximum operating temperature

60°C @ 2.8 bard (140°F @ 40 psid)

Recommended change-out differential pressure¹

2.4 bard (35 psid)

Product Specifications

Materials of construction

Filter media:	Bleached FDA-listed cotton, standard cotton, FDA-listed polypropylene ²
Center core:	Polypropylene
Sealing:	Thermal bond
O-rings:	Nitrile, fluorocarbon elastomer, hydrocarbon rubber, silicone elastomer



Dimensions (nominal)

Outside diameter:	6.4 cm (2.5 in)
Lengths:	25.4 cm (10 in), 50.8 cm (20 in), 76.2 cm (30 in), 102 cm (40 in)

¹ Provided that the maximum differential pressure is not exceeded based on temperature limits defined above.

² Please contact Pall Corporation to verify that the product conforms to your national legislation and/or regional regulatory requirements for water and food contact use.

Material Selection Guide

Material	Filter Medium	
	Cotton	Polypropylene
Polypropylene core	60°C (140°F) maximum temperature	60°C (140°F) maximum temperature
Potable liquids, water	Excellent	Excellent
Oils	Excellent	Good
Organic acids	Good	Excellent
Alkalies	Good	Excellent
Oxidizing agents	Fair	Poor
Strong inorganic acids	Not recommended	Excellent
Dilute inorganic acids	Fair	Excellent
Microorganism resistance	Poor	Excellent

Ordering Information

Pall Part Number = 1 2 AW 3 U 4 – M3

Table 1

Code	Filter medium
C	Bleached FDA-listed cotton
SC	Standard cotton
U	FDA-listed polypropylene

Table 2

Code	Filter grades (µm)
0.5	0.5
001	1.0
003	3.0
005	5.0
010	10
025	25

Table 3

Code	Cartridge lengths (cm/in) nominal
10	25.4 / 10
20	50.8 / 20
30	76.2 / 30
40	102 / 40

Table 4

Code	O-ring materials
S	Silicone
E	Hydrocarbon rubber
V	Fluorocarbon elastomer
N	Nitrile

LENNTECH

info@lenntech.com

www.lenntech.com

Tel. +31-15-261.09.00

Fax. +31-15-261.62.89

Pall Corporation has offices and plants throughout the world. For Pall representatives in your area, please go to www.pall.com/contact.

Please contact Pall Corporation to verify that the product conforms to your national legislation and/or regional regulatory requirements for water and food contact use.

Because of technological developments related to the products, systems, and/or services described herein, the data and procedures are subject to change without notice. Please consult your Pall representative or visit www.pall.com to verify that this information remains valid.

© Copyright 2005, 2010, Pall Corporation. Pall,  DFT Classic are trademarks of Pall Corporation. * indicates a trademark registered in the USA. Filtration. Separation. Solution.  is a service mark of Pall Corporation.